Sound Control Technologies

RemoteTableKit™ RTK-PLUS™ for Cisco Room Kit Application Guide

Updated: 5/12/2023

RTK-Transmitter™ Table Module

Cisco Microphones
Supports up to [2] Cisco Mics:
Cisco Mic 20 & Cisco Table-J

USB 2.0 Device (Client)
Uni-Directional Function can be used
at either end; See FAQ for more details.

Laptop
HDMI

Cisco Navigator or Touch10
Ethernet/POE
Cisco Provided

SCTLink™ Cable*
Ethernet/POE; Cisco Mic TRRS; HDMI;
Audio I/O & USB up to 100m CAT5e/CAT6

The **SCTLink™** cable must always be
a single, point-to-point CAT cable with
no couplers or interconnections.

Can be used on Tx or Rx.
WPS-12 30VDC
100-240V 47-63Hz
Power Supply

RTK-Receiver™ Codec Module

PC/Laptop USB 2.0 (Host)
Uni-Directional Function can be used
at either end; See FAQ for more details.

***SCTLink™ Cable Specs**
Integrator-Supplied CAT5e/CAT6 STP/UTP Cable
EIA568A or EIA568B (10m-100m min/max Length)

RCC-H001-1.0M
HDMI Cable

RCC-H016-1.0M
UTP Cable

RCC-C018-1.0M
TRRS to TRRS Cables

Cisco Room Kit

Module Dimensions
RTK-TX™: H: 1.39" (35mm) **x W:** 10.22" (259mm) **x D:** 4.51" (114mm)
RTK-RX™: H: 1.39" (35mm) **x W:** 10.22" (259mm) **x D:** 4.51" (114mm)