



FRONT

BACK

The USB-AMV combines USB data and an HDMI video input into a USB-C Full Function Alt-Mode video connection.

KEY FEATURES

- Combines HDMI and USB into a single USB-C connection to a codec or video bar.
- Frees up codec/video bar HDMI input.
- Passes USB video and bi-directional audio.
- Powered from codec or USB-C power supply.
- Simple Plug & Play installation, no programming or drivers required.

TECHNICAL SPECS

- Full Function USB Type-C: Locking USB-C jack supporting USB Video, audio, power, and DisplayPort Alt-mode video.
- Full Function USB Type-C Power: 3W sink to power USB-AMV, or 12W source when using USB-C Power Input.
- Video Format: DisplayPort 1.2a Transmitter Interface, HDMI In 4K@60 4:4:4, HDCP v2.3
- USB Pass-through Support: USB 3.1 Gen 2
- USB Tier Usage: No tiers.
- Power Input: Locking USB-C, 5W Minimum. Not needed if codec/video bar can source power.

MODULE & POWER SUPPLY SPECS

USB-AMV Module

- Imperial Dims: H: 0.85" x W: 2.91" x D: 4.11"
- Metric Dims: H: 22mm x W: 74mm x D: 104mm
- Weight: 0.26 lbs / 118g
- Power Consumption: 3W

SUPPORTED DEVICES

www.soundcontrol.net/product/usb-amv

PRODUCT WARRANTIES

www.soundcontrol.net/support

Included: 3 Year Standard Advance Replacement Limited Warranty

Available: 2 Year Extended Advance Replacement Limited Warranty



BUILT IN AMERICA



WITH U.S. & GLOBAL PARTS

TAA COMPLIANT

