



# Sound Control Technologies

## RCU2S-B10™ USB Application Guide

Updated: 02/27/2024

The **RCU2S-B10™** supports multiple camera models:

- AVer MD330u • MD330UI • PTC310UV2
- AVer TR311HWV2 • AVer TR313V2 • AVer TR323NV2
- AVer TR333NV2 • AVer TR530+ • AVer VB342 Pro
- ClearOne Unite 150 & 200
- Crestron IV-CAM-I12-B
- Huddlecam HC10X, HC20X & HC30X

- Lumens VC-B30U
- Marshall CV610-U3
- Minnray UV950A
- MaxHub UC P20
- PTZOptics 12XUSB & 20XUSB
- Sony SRG-120U & SRG-XP1

- Vaddio ConferenceShot FX
- Vaddio ConferenceShot 10
- VDO360 Saber20X & VDO360 CompassX
- VHD V20C, VX110, VX710N, VX710L & VX120
- Yamaha CS-700AV



Shown:  
**ClearOne Unite 200**

**RCU2S-HE™ Front Panel**  
Field-Upgradeable microSD Slot

**3.5mm Audio Cable**  
Integrator-Supplied

**PPC-023-0.3M**  
RJ11 (RCU2S-CE™)  
to EIAJ-4 Barrel

**RCC-M004-0.3M**  
USB-A (RCU2S-CE™)  
to USB-B

**RCC-M014-1.0M** Or **RCC-M004-1.0M**  
USB-B (RCU2S-HE™)  
to USB-C

Or **RCC-M004-1.0M**  
USB-B (RCU2S-HE™)  
to USB-A



**RCU2S-HE™**

**SCTLInk™ Cable**  
Power, Control & Video  
Refer to the RCU2S data sheet for cable specifications

**WPS-12 30VDC**  
100-240V 47-63Hz  
Power Supply



**RCU2S-CE™**

### Module Dimensions

**RCU2S-CE™:** H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)

**RCU2S-HE™:** H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)

