

The **RCU2S-BA8™** supports multiple camera models:

- | | | | | | |
|----------------------|-------------------------|---------------------|----------------------|-----------------------|--------------|
| • Angekis Saber Plus | • ClearOne Unite 150 | • Huddlecam HC20X | • Minnray UV950A | • VDO360 Saber20X NDI | • VHD VX110 |
| • AVer TR311HWV2 | • ClearOne Unite 200 | • Huddlecam HC30X | • PTZ Optics 12X USB | • VDO360 CompassX | • VHD VX710N |
| • AVer TR313V2 | • Huddlecam HC10X-GY | • Lumens VC-B30U | • PTZ Optics 20X USB | • VHD V71U2 | • VHD VX701L |
| • AVer TR323NV2 | • Huddlecam HC20X-GY/WH | • Marshall CV610-UB | • Sony SRG-120DU | • VHD V20C | • VHD VX120 |
| • AVer TR333NV2 | | | | | |

Shown: **ClearOne Unite 200**



3.5mm Audio Cable
Integrator-Supplied

RCC-C005-0.3M
RJ45 (RCU2S-CE™) Y Cable
to 4mm Power Barrel
to 8 Pin Mini Din

RCC-C006-0.4M*
RJ11 (RCU2S-CE™) to 8 Pin Mini Din

***Purchased Separately:**
*Cable required for VISCA Loop or
Daisy Chain Functionality. Do not connect to
last camera in Daisy-Chain. This will terminate
control on all cameras.*

RCU2S-HE™ Front Panel
Field-Upgradeable microSD Slot

RCC-M004-1.0M
USB-B (RCU2S-HE™)
to USB-A



RCU2S-HE™

SCTLINK™ Cable
Power, Control & Video
Refer to the RCU2S data
sheet for cable specifications

WPS-12 30VDC
100-240V 47-63Hz
Power Supply



RCC-M004-0.3M
USB-A (RCU2S-CE™)
to USB-B



RCU2S-CE™

Module Dimensions
RCU2S-CE™: H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)
RCU2S-HE™: H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)