



RCU2S-C10™ USB Application Guide

Updated: 02/17/2025



Supported Cameras:

- AVer PTC310
- AVer PTC310HN
- AVer TR310
- AVer TR311
- AVer TR311HN
- AVer TR313
- AVer TR331
- AVer TR333
- Marshall CV605-U3
- PTZ Optics Move SE
- Sony SRG-X40UH
- VHD M1000

RCU2S-HE™ Front Panel
Field-Upgradeable microSD Slot

RCC-M004-1.0M
USB-B (RCU2S-HE™)
to USB-A



Laptop



RCU2S-HE™

3.5mm Audio Cable
Integrator-Supplied

RCC-M005-0.3M
USB-A (RCU2S-CE™)
to USB-C

PPC-023-0.3M
RJ11 (RCU2S-CE™) to
EIAJ-4 Barrel Connector



RCU2S-CE™

SCTLINK™ Cable
Power, Control & Video
Refer to the RCU2S data sheet for cable specification

WPS-12 30VDC
100-240V 47-63Hz
Power Supply



Module Dimensions

RCU2S-CE™: H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)

RCU2S-HE™: H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)