



RemoteTableKit™ 8CP Product Specification

Updated: 2/12/2025



Sound Control Technologies (SCT) Table Extension Kits are designed to bring you the inputs from the Cisco Codec Pro backplane right to the table!

The RTK-8CP™ kit provides a reliable transparent audio link between the table microphones and the connected Cisco Codec Pro.

By simplifying complex cabling and extending traditional distance limitations up to 100', SCT's extension kit provides integrators with cost and time saving solutions.

KEY FEATURES

- Extends up to 8 Cisco Table Microphones over a standard CAT5e/CAT6 cable up to 100'.
- Flexibility to power the modules from either the transmitter or receiver.
- Simple Plug & Play installation, no programming required.
- [1] RM-PRO-M Cable Bundle supporting 4 Microphones included.
- Field-upgradable firmware via microSD Card.
- In high security environments, the microSD Card slot can be disabled.
- PowerSniffer included for testing SCTLINK™ cable conductor continuity.
- Integrator only required to provide a CAT5e/CAT6 SCTLINK™ Cable.

TECHNICAL SPECS

- Microphone Support: Up to 8 Cisco Microphone 60 or Microphone Table-E microphones.

SCTLINK™ CABLE SPECS

SCT recommends CAT6 or better cable for the SCTLINK™. The use of a shielded cable, while not required for most platforms, is highly recommended.

Proper termination and testing, along with good cable management, minimizes potential problems.

Wiring Termination Standard T568A or T568B
30' Minimum - 300' Maximum Length

Power Consumption

A linked stand-alone kit will consume 4.8W.

MODULE & POWER SUPPLY SPECS

RTK-8CP™ Transmitter Module

- Imperial Dims: H: 1.39" x W: 10.224" x D: 4.51"
- Metric Dims: H: 35mm x W: 259mm x D: 114mm
- Weight: 1.1 lbs / 498g

RTK-8CP™ Receiver Module

- Imperial Dims: H: 1.39" x W: 10.224" x D: 4.51"
- Metric Dims: H: 35mm x W: 259mm x D: 114mm
- Weight: 1.1 lbs / 498g

WPS-12™ Power Supply (Included)

- Imperial Dims: H: 1.19" x W: 1.85" x D: 4.65"
- Metric Dims: H: 30mm x W: 47mm x D: 118mm
- Weight: 0.5 lbs / 236g
- Input: 100 to 240VAC, 47-63Hz, 1.45A Max
- Output: 30VDC, 2A Max
- Output Connector: 5.5mm x 2.5mm DC Plug
- Regulatory Approvals:

UL, CE, FCC, CCC, TÜV, RCM+GEMS, LPS, BIS, PSE, CB, DoE VI, CoC V5 & RoHS2

SUPPORTED DEVICES

<https://www.soundcontrol.net/products/camera-extension-kits/remotetablekit-platform>

Cisco Codec Pro, Room 70 G2, and SX80 codecs.

Got questions? We've got answers. Check out our [FAQ's!](#)

RACK SHELVES

RC-RKM™ 2RU 12" Deep Rack Shelf

www.soundcontrol.net/product/rc-rkm-rack-shelf

- Designed to mount the RCU2-HE™, RC4-HE™, RC5-HE™, RC6-HE™, RC7-HE™, RC8-HE™, RTK-RX™ and RC-SDA™ modules, specific manufacturer codecs, and power supplies.
- Leaves access to rear of modules for clean and easy cabling.

PRODUCT WARRANTIES

www.soundcontrol.net/support

Included: 3 Year Standard
Advance Replacement
Limited Warranty

Available: 2 Year Extended
Advance Replacement
Limited Warranty



SOLUTION FINDER

Not sure where to start? Try our Solution Finder!
www.soundcontrol.net/solution-finder

