




The **RCU2E-C00™** supports multiple camera models:

- Panasonic AW-UE4
- Panasonic AW-UE20
- Panasonic AW-HE20
- Panasonic AW-UE20
- Panasonic AW-UE40
- Panasonic AW-UE50
- Poly E70
- PTZ Optics Move SE
- Sony SRG-X40

SCTLink™ Cable Specs

Integrator-Supplied CAT5e/CAT6 STP/UTP Cable
T568A or T568B (100m Max Length)



RCU2E-HE™ Front Panel

Field-Upgradeable microSD Slot

RCU2E-HE™




Poly Studio E70

RCC-M005-0.3M
USB-A (RCU2S-CE™) to USB-C

RCC-C002-0.3M
RJ45 (RCU2S-CE™) to RJ45

RCU2E-CE™



RCC-H016-1.0M
RJ45 (RCU2E-CE™) to RJ45

SCTLink™ Cable
Power, Control & Video

The **SCTLink™** cable must always be a single, point-to-point CAT cable with no couplers or interconnections.

RCC-M004-1.0M
USB-B (RCU2S-HE™) to USB-A
Or
RCC-M014-1.0M
USB-B (RCU2E-HE™) to USB-C

WPS-12 30VDC
100-240V 47-63Hz
Power Supply



Poly G7500



Module Dimensions

RCU2S-CE™: H: 0.789" (20mm) x W: 2.264" (57mm) x D: 3.725" (94mm)

RCU2S-HE™: H: 1.448" (36mm) x W: 3.814" (96mm) x D: 3.578" (90mm)