



RTK-AM1™ Transmitter Module



*Cables Included with Poly IP Table Microphone and TC8/TC10



Poly TC8/TC10



RCC-M015-2.0M
USB-C to USB-C USB Cable

WPS-48V4A 48VDC
100-240V 47-63Hz
Power Supply

SCTLINK2™ Cable*
Ethernet/POE; Cisco Mic Pro; HDMI;
Audio I/O & USB up to 100m CAT6A U/FTP
The **SCTLINK™** cable must always be
a single, point-to-point CAT cable with
no couplers or interconnections.

RTK-AM1™ Receiver Module




RCC-M015-1.0M
HDMI to HDMI Cable

RCC-M015-1.0M
USB-C to USB-C USB Cable

WPS-12 30VDC
100-240V 47-63Hz
Power Supply

[2] RCC-H016-1.0M
RJ45 to RJ45 UTP Cable

***SCTLINK2™ Cable Specs**
Integrator-Supplied CAT6A U/FTP Cable
EIA568A or EIA568B (10m-100m min/max Length)



Module Weights & Dimensions

RTK-AM1™ TX: (18.5oz) H: 1.30" (33mm) x W: 10.5" (267mm) x D: 4.5" (115mm)
RTK-AM1™ RX: (16.5 oz) H: 1.30" (30mm) x W: 10.1" (257mm) x D: 4.5" (115mm)